

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **60014208 A**

(43) Date of publication of application: **24.01.85**

(51) Int. Cl.

**G02B 6/44**

**C03C 25/02**

(21) Application number: **58121992**

(22) Date of filing: **05.07.83**

(71) Applicant: **FURUKAWA ELECTRIC CO LTD:THE**

(72) Inventor: **SHIRASAKA ARIO  
FUSE KENICHI**

(54) **COATED OPTICAL FIBER**

cable, etc.

(57) Abstract:

COPYRIGHT: (C)1985,JPO&Japio

PURPOSE: To prevent longitudinal crack and to obtain a high transmission characteristic by providing a resin layer between a buffer layer provided on the outside circumference of an optical fiber and a reinforcing coat layer formed on the outside thereof and adhering the resin layer and the reinforcing coat layer.

CONSTITUTION: A resin layer 4 is interposed between a buffer layer 3 provided on the outside circumference of an optical fiber 1 and a reinforcing resin (FRP) layer 5 consisting of fiber-reinforced plastics. The resin layer 4 and the FRP layer 5 are adhered. The resin layer 4 is preferably formed of a curable resin. The resin layer 4 of the optical fiber having such constitution supports the FRP layer 5 and suppresses the deformation of the FRP layer 5 and therefore the mechanical characteristic of the fiber is improved and the incidence of generating longitudinal crack is decreased. The microbend occurring in the FRP layer 5 is prevented by such resin layer 4 and therefore the high transmission characteristic of the coated optical fiber is assured and the fiber is used for a core for an underground buried communication

